



# Wireless DC Current Probes

The **RxMS** Wireless system is a data logging tool that is utilized to monitor multiple points in your system as well as the operating environment surrounding it.



## DC Current Probe Specifications:

12V DC powered

+/- 2,000A	+/- 4,000A
Resolution: 0.017 A	Resolution: 0.035 A
Accuracy: $\pm 0.5\%$	Accuracy: $\pm 0.5\%$

- Sample speed 1 second
- Min, Max, Avg logging

-Hall effect probe powered from system **no batteries required!**



## 4000A 4.5"x2.5" ID Probe Specifications:

- Range: 40-4,000 ADC / 28 -2,800 AAC

0-5,000 Hz

- Accuracy:


Noise: +/- 2ADC

1.5% from 400-4,000ADC

2% from 40-400ADC

4% from 8-40ADC

Operating Conditions: 14-122 ° F / Max 600V



## 2000A 2" ID Probe Specifications:

- Range: 20-2,000 ADC / 14 -1,400 AAC

0-5,000 Hz

- Accuracy:

Noise: +/- 1 ADC

1.5% from 200-2,000ADC

2% from 20-200ADC

4% from 4-20ADC

Operating Conditions: 14-122 ° F / Max 600V

## Additional Product Information:

- Individual log file created for each probe
- Programmable log rate of 4 Seconds to 30 minutes
- Over 100 probes per monitor, mix and match probe types
- Range: Indoor up to 100 ft
- Line of Sight up to 1 mile
- External power supply for long term install
- Magnetic backing for easy placement
- "Notes Feature" ideal for identifying and tracking of probes location. (Faster reporting of data)
- Dimensions: 3" x 4.5" x 1.5" (L/H/W)



THIS INFORMATION IS PROPERTY OF  
 RX MONITORING SERVICES, INC. • 22A EASTMAN AVE BEDFORD NH 03110-6701  
 TELEPHONE: (603) 666-6606 • 24HR TECH SUPPORT: EXT. 2 • WEB: WWW.RXMS.COM

